

TITLE OF THE INVENTION

5

**Resorbable Interbody Spinal Fusion Devices**

CROSS REFERENCE TO RELATED APPLICATIONS

10 This application claims priority from U.S. Patent Application No. 09/131,716, filed August 10, 1998; and from U.S. Provisional Patent Application Nos. 60/055,291, filed August 13, 1997; 60/074,076, filed February 9, 1998; 60/074,197, filed February 10, 1998, and 60/081,803, filed April 15, 1998, the entire disclosures of which are incorporated herein by reference.

15

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable

20

BACKGROUND OF THE INVENTION

The present invention relates to the field of interbody spinal fusion devices.

25 In the structure of the spine of vertebrates including humans, the space between adjacent vertebrae is referred to as the interbody space. In normal spines, this space is occupied by the structure commonly referred to as a disc. This intervertebral structure separates and cushions the vertebrae.

30 Various pathologic and traumatic conditions require excision of a spinal disc and stabilization of the superior and inferior vertebrae while bony fusion develops. In 1995, approximately 225,000 new spinal fusions were performed in the United States alone, and of these about one half were performed in the thoracic and 35 cervical spine, with the remaining spinal fusions focused on the lumbar spine. To stabilize the spine where the

5 surgery has occurred, an internal fixation device is frequently used. Such implants provide the ability to improve spinal alignment and maintain the developing alignment while fusion develops. Fixation of the spine can further correct deformity and provide immediate stability, thereby facilitating spinal fusion, early mobilization, and, when necessary, entry into rehabilitative programs.

10 The use of fixation devices is beneficial in several ways. First, the avoidance of long-term bed rest, thought by many to decrease non-neurological morbidity, is achieved. Additionally, fixation devices are thought to promote fracture healing and therefore reduce the need for rigid and cumbersome post-operative bracing.

15 While a number of commercially available implants for spinal stabilization are known, these devices are not resorbable and therefore, remain permanently at the implant site. Meticulous bone preparation and grafting is essential for successful long-term stability using current devices. Metallic and graphite implants have been known to fatigue and will eventually fail if the desired solid bony fusion is not achieved. Thus, it would be advantageous to obtain successful bony fusion and spinal development while avoiding the use of devices having the  
25 aforementioned drawbacks.

#### SUMMARY OF THE INVENTION

The present invention is directed to resorbable interbody fusion devices for use as spacers in spinal fixation, wherein the device is composed of 25-100% bioresorbable or resorbable material. The devices can be in any convenient form, such as a wedge, screw or cage. In one embodiment, the interbody fusion device of the invention further desirably incorporates structural  
35 features such as serrations to better anchor the device in the adjoining vertebrae. In another embodiment, the

device comprises a plurality of peripheral voids and more desirably a central void space therein, which may desirably be filled with a grafting material for facilitating bony development and/or spinal fusion, such as an autologous grafting material. In addition, void spaces increase the surface area of the device, thereby providing multiple sites for resorption to occur.

In yet another embodiment, the interbody fusion device of the invention further includes reinforcing fibers to enhance the structural properties thereof. These fibers may be made of the same polymeric material as the resorbable material from which the interbody fusion device is made, from a neutralization compound or, alternatively, from another biocompatible polymer, which may be crosslinked with a suitable crosslinking agent to yield an interpenetrating network for increased strength and stability. In another alternative embodiment, the reinforcing fibers are incorporated into the device, e.g., during the molding process, being placed in the mold under tension and released after the process of molding is complete.

Bioerodible polymers that are useful in the invention include polydioxanone, poly( $\epsilon$ -caprolactone); polyanhydride; poly(ortho ester); copoly(ether-ester); polyamide; polylactone; poly(propylene fumarate) ( $H[-O-CH(CH_3)-CH_2-O-CO-CH=CH-CO-]_nOH$ ); and combinations thereof.

In a preferred embodiment, the polymer poly(lactide-co-glycolide) (PLGA:  $H[-OCHR-CO-]_nOH$ ,  $R=H, CH_3$ ), with a lactide to glycolide ratio in the range of 0:100% to 100:0% inclusive, is used.

As many of the preferred bioerodible polymers from which the resorbable interbody fusion device is manufactured are polymers that can produce acidic products upon hydrolytic degradation, the device preferably further includes a neutralization compound, or buffer. The neutralization compound is included in sufficiently high

concentration to decrease the rate of pH change as the device degrades, in order to prevent sterile abscess formation caused by the accumulation of unbuffered acidic products in the area of the implant. Most preferably, the buffering or neutralizing agent is selected from a group of compounds wherein the pKa of the conjugate acids of the buffering or neutralization compound is greater than the pKa of the acids produced by hydrolysis of the polymers from which the device is prepared.

The neutralization compound, or buffer, included in the bioerodible material of the invention may be any base, base-containing material or base-generating material that is capable of reacting with the acidic products generated upon hydrolysis of the bioerodible polymer. Polymeric buffers which preferably include basic groups which neutralize the acidic degradation products may also be used as buffering compounds. Another class of useful buffering compounds are those which, on exposure to water, hydrolyze to form a base as one reaction product.

In another alternative embodiment, the resorbable interbody fusion device of the invention preferably includes a biological growth factor, e.g., bone morphogenic protein, to enhance bone cell growth. To protect the growth factor and to provide for controlled delivery, the biological growth factor may itself be compounded with a resorbable polymer in some of the many techniques available and prepared as a growth factor/polymer composite in pellet form, in small particle form or within the interstices or pores of a polymeric foam or low-density polymer and this polymer/growth factor composite is deposited into void spaces of the resorbable spinal fusion device. Alternatively, the growth factor, or protected growth factor, may simply be directly incorporated into the component formulation of the resorbable spinal fusion device.

Active periosteum cells may also be incorporated into

a foam, e.g., deposited into void spaces of the resorbable spinal fusion device, in order to facilitate bone cell fusion. Further, the resorbable spinal fusion device of the invention may be prepared in such a manner as to exhibit a piezoelectric effect, to enhance bone wound healing.

As used herein, the terms "resorbable" and "bioresorbable" are defined as the biologic elimination of the products of degradation by metabolism and/or excretion and the term "bioerodible" is defined as the susceptibility of a biomaterial to degradation over time, usually months. The terms "neutralization compound" or "buffer" are defined as any material that limits or moderates the rate of change of the pH in the implant and its near environment upon exposure to acid or base. The term "acidic products" is defined herein as any product that generates an aqueous solution with a pH less than 7.

#### DESCRIPTION OF THE DRAWINGS

The invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings in which:

Figs. 1A, 1B and 1C are perspective top, side and front views, respectively, of an interbody spinal fusion device according to the present invention;

Figs. 2A, 2B and 2C are top, side and perspective views, respectively, of another embodiment of an interbody spinal fusion device of the invention;

Figs. 3A, 3B and 3C are top, side and perspective views, respectively, of another embodiment of an interbody spinal fusion device of the invention;

Figs. 4A and 4B are side and top views, respectively, of another embodiment of an interbody spinal fusion device of the invention;

Figs. 5A and 5B are side and top views, respectively, of another embodiment of an interbody spinal fusion device

of the invention;

Fig. 6A is a perspective view of a mold and ram assembly for preparing an interbody spinal fusion device of the invention;

5 Figs. 6B and 6C are edge and plan views, respectively, of the front face plate of the mold of Fig. 6A;

Fig. 6D shows a disc with serrated slots for use in the mold of Fig. 6A;

10 Figs. 6E and 6F are front and side views, respectively, of a threaded tension tube used with the mold of Fig. 6A;

Fig. 6G is a section through a mold assembly fitted with reinforcing fibers and associated holder assemblies;

15 Fig. 7 is a plot of displacement versus load for an interbody spinal fusion device of the invention; and

Fig. 8 shows compression strength with load for interbody spinal fusion devices of the invention with and without the incorporation of a buffering or neutralizing compound.  
20

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention provides, in one embodiment, an interbody spinal fusion device (IFD) comprising a  
25 resorbable spinal wedge for vertebral spacing as an adjunct to spinal fusion. Made from a biodegradable, biocompatible polymer, preferably poly(lactic-co-glycolic) acid (PLGA), discussed further below, this resorbable spacer incorporates peripheral voids and central voids,  
30 which can be filled with autologous grafting material to facilitate bony development and spinal fusion, and serrated or threaded faces to stabilize and align vertebral bodies. The spinal fusion device of the invention is used as an adjunct to fusions of the  
35 cervical, thoracic or lumbar vertebrae, the configuration and dimensions of the device depending on the site of use.

A preferred embodiment of a spinal implant, fabricated from a biocompatible and biodegradable polyester and intended to replace a cervical disc, C4, 5, or 6, is shown in Figs. 1A, 1B and 1C. A rod molded from a suitable material, as described below, is machined to the desired configuration and dimensions. Relatively complex geometries can be readily fabricated in this manner. Suitable biocompatible extraneous materials such as plasticizers or other machining aids, can be included in the material if desired.

As shown in Fig. 1A, a preferred resorbable interbody spinal fusion device of the invention 10 is in the shape of a tapered wedge, having a top face 11, a bottom face 12, side faces 13, a front end 14 and a back end 15. The surfaces of top and bottom faces 11 and 12 each have serrations 16 to aid in anchoring the device to the surrounding bone. Wedge 10 preferably contains holes 17 of convenient diameter, which may be drilled through the wedge to facilitate resorption of the polymer from which the device has been made. A plurality of channels or ports 18 through the wedge or a larger center hole 19 in the wedge are useful for the introduction of autologous bone. As illustrated in Figs. 1B and 1C, the spinal wedge is preferably machined to have a taper from back end 15 to front end 14, such that the front end 14 is narrower than the back end 15.

In another embodiment, as shown in Figs. 2A-2C resorbable spinal fusion device 20 is shaped like a tapered rod having ridges 22 with threads 21. Device 20 functions as a screw and contains a cylindrical axially extending hole 23 and slots 24 to facilitate screwing the device into the spine of the patient. The device also contains recesses 26 between ridges 22 to facilitate ingrowth of tissue that would aid in anchoring the device in place.

As shown in Figs. 3A-3C, in a further embodiment, the

device 30 is of cruciform shape having arms 33. Threads 31 extend the length of the outer surfaces of arms 33. In another embodiment, shown in Figs. 4A-4B, the device is shaped like a threaded screw having a continuous thread 41 provided around the surface of the tapered body. Cylindrical holes 43 and 44 are provided through the body, the holes being orthogonal to each other and to screw axis 42. A cylindrical hole 45 is provided coaxially with axis 42. Slots 46 in the top 48 serve to position and retain a tool that can be used to screw the device into place.

As shown in Figs. 5A and 5B, a further embodiment of a threaded screw contains flat side areas 52 alternating with threaded corner areas 51. Slots 53 can be machined or otherwise provided in the flat areas, to facilitate ingrowth of tissue, and can be of a constant width or can be tapered. A slot 56 in top 58 of the device accommodates a suitable tool to facilitate insertion.

For replacement of one of the cervical discs C4, C5, or C6, the device shown in Figs. 1A-1C preferably measures 15 mm laterally by 12 mm sagittally. The flattened side, positioned posteriorly, is 6-8 mm thick, enlarging to about 7-9 mm at the anterior edge; thus the device has a taper of approximately 4.8 degrees. Both surfaces are serrated, the serrations directed laterally. The serrations may be either square cut or cut at an angle with one face vertical and the other sloping upward anteriorly.

The thickness of the device of the invention will govern the rate at which it degrades and total degradation time. Thus, interbody spinal fusion devices can be prepared with multiple thicknesses, but all having the same approximately 5° taper. For example, the anterior thickness could range from 7 to 9 mm and the posterior thickness from 6 to 8 mm. The taper provides the correct orientation to the vertebrae with which the device is in contact and can also serve to keep the device in place.



The vertebral body is a fairly cylindrical mass consisting of cancellous bone surrounded by a thin layer of cortical bone. Thus, the mechanical properties of the device should preferably match those of the cancellous bone of the vertebrae in regard to proportional limit stress, compression at proportional limit, modulus of elasticity, failure stress and compression at failure (See, e.g., Lindahl, Acta Orthop. Scand. 47:11, 1976; Hansson et al., Spine 12:56, 1987).

Bioerodible polymers that are useful in the spinal fusion device of the invention include polydioxanone, poly( $\epsilon$ -caprolactone); polyanhydride; poly(ortho ester); copoly(ether-ester); polyamide; polylactone; poly(propylene fumarate) ( $H[-O-CH(CH_3)-CH_2-O-CO-CH=CH-CO-]_nOH$ ); poly(lactic acid); poly(glycolytic acid); poly(lactide-co-glycolide); and combinations thereof. Selection of a particular polymer is based primarily on the known properties of the polymer, such as the potentiality for cross-linking, polymer strength and moduli, rate of hydrolytic degradation, etc. One of ordinary skill in the art may take these and/or other properties into account in selecting a particular polymer for a particular application. Thus, the selection of a particular polymer is within the skills of the ordinary skilled practitioner.

In a preferred embodiment, the polymer poly(lactide-co-glycolide) ( $H[-OCHR-CO-]_nOH$ ,  $R=H, CH_3$ ) (PLGA) is used. The PLGA polymers used according to the invention desirably have a lactide to glycolide ratio in the range of 0:100% to 100:0%, inclusive, i.e., the PLGA polymer can consist of 100% L- or D,L-lactide (PLA), 100% glycolide (PGA), or any combination of lactide and glycolide residues. These polymers have the property of degrading hydrolytically in vivo to form organic acids (lactic acid and glycolic acid) which accumulate in the region surrounding the implant. These acids are metabolized and

eventually excreted as carbon dioxide and water or enter the citric acid cycle.

5 The process by which alpha polyesters such as PLA, PGA, and PLGA biodegrade is primarily by non-specific hydrolytic scission of the ester bonds. The L-lactic acid that is generated when PLA or PLGA degrades becomes incorporated into the tricarboxylic acid cycle and is excreted from the lungs as carbon dioxide and water. Glycolic acid, produced both by random hydrolytic scission and by enzymatically mediated hydrolysis, may be excreted in the urine and also can enter the TCA cycle and eventually be oxidized to carbon dioxide and water (Hollinger et al., Clin. Orthop. Rel. Res. 207: 290-305, 1986).

15 A particularly preferred polymer for use in the device of the invention is poly(d,l-lactide-co-glycolide)-85:15 (Boehringer-Ingelheim: distributor, Henley Chemicals, Inc., Montvale, NJ), the 85:15 designation referring to the lactide to glycolide mole ratio. The particularly preferred polymer is Resomer™ RG 858, with an inherent viscosity of approximately 1.4 corresponding to a weight average molecular weight of 232,000 as measured by gel permeation chromatography (GPC).

25 The polymer can be used as received or purified by precipitation from tetrahydrofuran solution into isopropanol, air dried and then exhaustively vacuum dried. Polymer data (composition and molecular weight) can be confirmed by nuclear magnetic resonance and by GPC (Hsu et al., J. Biomed. Mater. Res. 35:107-116, 1997).

30 Spinal fusions require interbody fusion devices that will maintain significant structural rigidity for 6-12 months. Strength requirements depend on the location of the disc to be replaced. When a person is standing, the forces to which a disc is subjected are much greater than the weight of the portion of the body above it. Nachemson

35

et al. (Acta. Orthop. Scand. 37:177, 1966; J. Bone Joint Surgery 46:1077, 1964; Clin. Orthop. 45:107, 1966) has determined that the force on a lumbar disc in a sitting position is more than three times the weight of the trunk.

- 5 Daniels et al. (J. Appl. Biomater. 1:57-78, 1990) have reviewed much of the mechanical data of PGA, PLA, and PLGA.

As a bioerodible polymer undergoes hydrolysis in the body, any acidic degradation products formed may be  
10 implicated in irritation, inflammation, and swelling (sterile abscess formation) in the treated area. To counteract this effect, a neutralization compound, or buffer, is desirably included in the bioerodible material to neutralize the acidic degradation products and thereby  
15 reduce the sterile abscess reaction, as described in copending U.S. Application No. 08/626,521, filed April 3, 1996, the whole of which is hereby incorporated by reference herein.

The buffering compound included in the bioerodible  
20 material of the invention may be any base, base-containing or base-generating material that is capable of reacting with the acidic products generated upon hydrolysis of the bioerodible polymer. Exemplary buffering materials include salts of inorganic or organic acids, salts of  
25 polymeric organic acids or polymeric bases such as polyamines. Preferably calcium salts of weak acids such as, e.g., tribasic calcium phosphate, dibasic calcium phosphate, or calcium carbonate are use. To be useful, the conjugate acids from which the buffering materials are  
30 derived must have a pKa greater than those of L-lactic acid (pKa = 3.79), D, L-lactic acid (pKa = 3.86), or glycolic acid (pKa = 3.83), if a PLGA is the polymer which is undergoing hydrolysis. Thus, for example, salts of acetic acid (pKa = 4.74), or succinic acid (pK<sub>1</sub> = 4.19, pK<sub>2</sub>  
35 = 5.64) may also be used.

Buffer compositions of lower solubility are preferred

because buffer loss from the polymer by diffusion will be slower (Gresser and Sanderson, "Basis for Design of biodegradable Polymers for Sustained Release of Biologically Active Agents" in Biopolymeric Controlled  
5 Release Systems, Ch. 8, D.L. Wise, Ed., CRC Press, 1984).



Preferably, the buffering compound has an acid dissociation constant that is smaller than the acid dissociation constant of the acidic products generated upon hydrolysis of the bioerodible polymer. Ionic buffers  
10 will, in general, be the salts of weak acids. The acid, of which the buffer is a salt, should have an ionization constant (acid dissociation constant,  $K_a$ ) which is less than the  $K_a$  for the acid products of polymer hydrolysis. Alternatively, the buffering compound has a hydrolysis  
15 constant that is greater than the hydrolysis constant of the acidic products.

Hydroxyapatite (HA) and calcium carbonate (CC) were each investigated as buffering fillers. Results demonstrate that the inclusion of CC or HA in a, e.g.,  
20 PLGA fixture can effectively moderate the rate of pH decline as the fixture degrades. Further, the rapid decline in pH can be offset without considering 100% neutralization of the lactic and glycolic components. Thus, even given that the polymeric fixture will be filled  
25 with an inorganic buffer, the mechanical characteristics of the fixture can be stabilized since the loading requirements for the buffer will not be nearly as compromising as expected at the outset.


While both CC and HA can ameliorate the rate of decline in pH in the region of polymer hydrolysis, the use  
30 of hydroxyapatite as a filler also supports osteoconductivity. Thus, HA not only promotes bony ingrowth and obviates loosening of the fixture, but also acts as a buffer thereby preventing the formation of  
35 sterile abscesses that have been attributed to the acidic degradative products of PLGA implants. The resulting

resorbable fixture should be capable of a buffered hydrolytic degradation and induction of bony ingrowth as resorption of the implant progresses. A resorbable buffered bone fixture with such properties could provide structural support to stabilize and support a spinal repair over the period of time required for natural healing to occur.

According to the invention a preferred buffering compound is hydroxyapatite. The formula  $\text{Ca}_{10}(\text{OH})_2(\text{PO}_4)_6$  may be written as  $\text{Ca}(\text{OH})_2 \cdot 3\text{Ca}_3(\text{PO}_4)_2$ . When written in this manner it is seen that the following neutralization reactions may be written:



The dissociation constant of water (the conjugate acid of the hydroxyl ion) is  $K_w = 10^{-14}$ . The basic phosphate ion,  $\text{PO}_4^{-3}$ , can neutralize two protons forming the following acids, for which dissociation constants are given:



$$K_2 \text{ of } \text{H}_2\text{PO}_4^{-1} = 6.2 \times 10^{-8}$$

$$K_3 \text{ of } \text{HPO}_4^{-2} = 4.2 \times 10^{-13}$$

Buffers included in the polymer in solid form preferably have a relatively small particle size, for example, between less than 1.0 and 250  $\mu\text{m}$ . Particle size reduction can be accomplished by any standard means known in the art, such as ball milling, hammer milling, air milling, etc. If buffer and polymer are to be blended by the dry mixing method (described below), the polymer particle size must also be considered. Polymers such as the PLGAs have relatively low glass transition temperatures and melting temperatures. Thus, polymer particle size reduction must be accompanied by cooling, for example using a Tekmar A-10 mill with a cryogenic

attachment.

Following milling, the desired particle size range of the buffer and the polymer may be recovered by sieving through, for example, U.S. Standard sieves. Particles in  
5 the size ranges of <45, 45-90, 90-125, 125-180, 180-250  $\mu\text{m}$  may be conveniently isolated.

In selection of particle size range, it is sometimes desirable to combine two or more ranges, or to use a wide range of sizes, for instance all sizes less than 250  $\mu\text{m}$ .  
10 Larger particles may be preferred in some applications of the invention because larger particles take longer to be eroded by the acids and will therefore extend the useful lifetime of the buffer. In some cases particle size reduction will not be necessary, such as when commercially  
15 available precipitated calcium carbonate is used (e.g., Fisher Scientific, Inc., Catalog No. C-63).

The effectiveness of substances such as calcium carbonate and hydroxyapatite in neutralizing the acid products of polymer hydrolysis depends not only on the  
20 quantity of the substance in the matrix, but also on particle size and distribution, total surface area in contact with the polymer, and solubility.

The presence of calcium ions in the buffered device has advantages with respect to the physical properties of  
25 the device as it undergoes erosion. It has been shown that calcium ions form ionic bridges between carboxylate terminal polymer chains (Domb et al., J. Polymer Sci. A28, 973-985 (1990); U.S. Pat. No. 4,888,413 to Domb). Calcium ion bridges between carboxylate anions increase the  
30 strength of the composite in which the polymer chains are terminated by carboxylate anion end groups over similar chains terminated by the hydroxyl groups of, e.g., terminal glycol moieties or terminal  $\alpha$ -hydroxy acids. In an analogous manner, the polyesters comprising the family  
35 of PLGA's are expected to be strengthened by calcium bridges between carboxylate anion terminated chains. As

shown in Fig. 8 PLGA-85:15 wedges reinforced with 40% HA showed an increase in compressive strength of approximately 5% over the nonreinforced controls.

Another class of useful buffering compounds are those which, on exposure to water, hydrolyze to form a base as one reaction product. The generated base is free to neutralize the acidic products produced upon hydrolysis of the bioerodible polymer. Compounds of this type include aryl or alkyl carbamic acids and imines. These "base-generating compounds" offer the advantage that the rate of hydrolysis of the base generator may be selected to correlate to the rate of hydrolysis of the bioerodible polymer.

Necessarily, the conjugate acid of the buffering compound has an acid dissociation constant that is smaller than the acid dissociation constant of the acidic products generated upon hydrolysis of the bioerodible polymer. Alternatively, the buffering compound preferably has a hydrolysis constant that is greater than the hydrolysis constant of the acidic products.


Furthermore, the buffering compound preferably is only partially soluble in an aqueous medium. In general, buffers of lower solubility are preferred because buffer loss from the polymer by diffusion will be minimized (Gresser and Sanderson, supra). The quantity of buffer to include depends on the extent of neutralization desired. This may be calculated as shown below, using a PLGA of any composition buffered with calcium carbonate as an example.

The average residue molecular weight, RMW, for a PLGA is given by

$$\text{RMW} = 14.03x + 58.04$$

where  $x$  = mole fraction of lactide in the PLGA. The term "residue" refers to the repeating lactide or glycolide moiety of the polymer. For example, if  $x = 0.85$  (PLGA=85:15),  $\text{RMW} = 69.96$ . Thus, 1.0 gram of PLGA=85:15 contains 0.01429 moles of residues which, on hydrolysis of

the polymer, will yield 0.01429 moles of lactic and/or glycolic acid. If, e.g., calcium carbonate is the buffering agent, and it is desired to neutralize, e.g., 50 mole % of the acids by the reaction



where A = lactate or glycolate, then the weight of calcium carbonate needed is  $(0.25)(0.01429)(100.09) = 0.358$  gram, and the required loading is  $(0.358)(1 + 0.358)(100) = 26.3\%$  by weight.

10                Several methods may be used to incorporate the buffer into the polymer. These methods include solution casting coupled with solvent evaporation, dry mixing, incorporating the buffer into a polymer foam, and the polymer melt method.

15                Solution casting coupled with solvent evaporation may be used with buffers which are either soluble or insoluble in the solvent. The bioerodible polymer is dissolved in any suitable volatile solvent, such as acetone, tetrahydrofuran (THF), or methylene chloride. The buffer, 20 which may be soluble or insoluble in this solvent, is added to give the final desired ratio of polymer to buffer. If particle size reduction of the buffer is necessary, it may be accomplished by ball milling the suspension of buffer in the polymer solution. In 25 contrast, if the buffer is soluble in the chosen solvent, particle size reduction at any stage is not necessary.

                 The suspension or co-solution is cast as a film on a glass or other inert surface, and the solvent is removed by air drying. Residual solvent remaining in the film may 30 be further removed by subjecting the film to vacuum drying at elevated temperatures. As an example, if calcium carbonate is to be used as a buffering compound and it is desired to neutralize 50% of the acid formed by hydrolysis of PLGA-50:50, the buffer content of the composition 35 should be 27.8%.



In an exemplary embodiment, to prepare 50 grams of composite, 36.1 grams of PLGA-50:50 are dissolved in approximately 250 ml of tetrahydrofuran, and 13.9 grams of calcium carbonate of the desired particle size range is added to the solution mixture. After distributing the calcium carbonate homogeneously by mixing, the suspension is dried to a film as described above.

The resulting film may be processed by compaction under high pressure, extruded through a die, injection molded, or other method known in the art. Further definition of the final shape may be accomplished at this point by any desirable machining process, such as lathing.

In the dry-mixing method, a polymer of appropriate particle size range is mixed with the buffer, also of chosen particle size range, in proportions to give the desired stoichiometric buffering capacity. The dry mixture is thoroughly blended by rotating the mixture in a ball mill jar from which the grinding balls have been omitted, or other suitable mixing device. The blended mixture may then be processed by compaction, extrusion, injection molding, etc., as described above.

In the polymer melt method, a known weight of the buffer is incorporated by mixing into a known weight of a suitable melted polymer. A quantity of polymer is heated to a temperature above its melting point, and a suitable buffer is blended into the melted polymer. The resulting polymer/buffer composite is solidified by cooling, and may be processed as described above, or ground and sieved prior to processing.

In some applications, it may be desirable to protect the buffering compound, for example, during processing according to the melt method, or to make the buffering compound available at the later stages of polymer degradation. In such cases, it is desirable to coat the buffering compound particles with a material that degrades at a slower rate than the material chosen for the fixation

devices. Thus, the buffering compound is exposed only after the body of the device and the coating material have partially degraded. Exemplary materials used to coat the buffering compound particles include high molecular weight poly(L-lactide) or poly( $\epsilon$ -caprolactone).

The particles of buffering compound may be coated with the protective material by any method that coats particles, such as spray coating with a solution of protecting polymer or micro-encapsulation. Alternatively, a chosen protective polymer may be made in a melted state and buffer particles are added. The melt is cooled and ground and milled to the desired particle size range. Alternatively, the buffering compound may be added to a solution of the protective polymer and removing the solvent by evaporation. The dried mass is compacted in a mold under high pressure and grinding or milling the compacted mass to the appropriate particle size range.

The resorbable spinal fusion device of the invention optionally includes a biological growth factor, e.g., bone morphogenic protein, to enhance bone cell growth. To protect the growth factor and to provide for controlled delivery, the biological growth factor may be itself compounded with a resorbable polymer by one of the many techniques available and prepared as a growth factor/polymer composite in pellet form, in small particle form or within the interstices or pores of a polymeric foam or low-density polymer and this polymer/growth factor composite deposited into void spaces of the resorbable spinal fusion device. Alternatively, the growth factor may simply be directly incorporated into the component formulation of the resorbable spinal fusion device.

Active periosteum cells, or other bony cells, may be also incorporated into a foam surrounding, or deposited in, the resorbable spinal fusion device so that the cells may facilitate bone cell fusion. To carry out such an incorporation, the periosteum surrounding a human bone is

removed and cultured following standard cell culturing techniques. The scaffold for such periosteum cell growth is a resorbable polymer foam or mesh. This scaffolding is prepared by dipping the completed device in a polymer/solvent (such as PLGA dissolved in acetic acid). The so-wetted device is then frozen and subsequently freeze-dried (lyophilized) resulting in a foam layer (or coating) of polymer surrounding the device. After the periosteum cells have been grown in this foam layer, the device is incorporated into the spine for the enhancement of spinal fusion.

In another embodiment, the resorbable spinal fusion device may be prepared in such a manner as to exhibit a piezoelectric effect. It is known that oriented (molecularly aligned) biopolymers such as PLGA have piezoelectric characteristics. In addition, the oriented biopolymer poly-L-lactic acid (PLLA) has been shown to promote bone wound healing (Shimono et al., *In Vivo* 10:471-476, 1996 and Ikada et al., *J. Biomed. Mater. Res.* 30:553-558, 1996). To take advantage of this phenomenon, the resorbable polymer is first aligned, by drawing, for example, such that all polymer chains are essentially parallel. The spinal fusion device is then cut from this aligned polymeric material such that the polymer chains are at approximately a 45° angle to the surface of the device, this angle being known to produce the optimal piezoelectric effect. Buffers, reinforcement materials, growth factors, etc., may also be included in processing of the spinal fusion device to exhibit this phenomenon.

As described by White et al. (*Clinical Biomechanics of the Spine*, 2nd edition, 1990), there are four stages of maturation of the arthrodesis (spinal fusion): I, fibrous healing; II, mixed fibrous and osseous healing; III, immature osseous healing; and IV mature osseous healing. Stage I requires maximum protection with restricted

activity and perhaps a protective orthosis. During stage II relatively less protection is required although with restricted activity. During stage III the patient is allowed normal but nonvigorous activity. In stage IV, maximum healing will be reached. For clinically stable patients the first three stages require about six weeks each, and stage IV, a minimum of six weeks. Clinically unstable patients require more time, especially for the first two stages. Thus the goals for duration and strength may be estimated.

A prototype device has been prepared for in vitro determination of weight loss and failure strength as a function of time. Due to the asymmetric design of the IFD, it is not feasible to measure the compressive modulus over time of the in vitro prototypes. This parameter, as well as failure and ultimate strength over time in vitro, has been measured on cylindrical discs of the same overall dimensions. In vitro experiments permit monitoring of the change in molecular weight in time for correlation with the mechanical measurements. Devices are tested for mechanical properties, e.g., compressive strength, compressive modulus, with equipment such as, e.g., the TA-XT2 Texture Analyzer (Texture Technologies Corporation) or the Instron 8511 Servo-Hydraulic System (Instron Corp.).

PLGA-85:15 (Resomer RG 858) including reinforcing fibers and HA buffer was molded at approximately 50°C under a force of 7-9 tons to form a translucent cylindrical rod 1.6 cm in diameter and 5.0 cm in length. Devices were then machined to the appropriate final dimensions, as discussed earlier. White and Panjabi (p. 29) report dimensions and stresses to which thoracic vertebrae are subject. The average area of the upper and lower end plates of T1 is about 340 mm<sup>2</sup>, and is subject to a loading force of about 2000 N. The compressive strengths of exemplary buffered and reinforced devices were, in all

cases, greater than 13,000 N. Thus, the initial strength of these PLGA-85:15 devices is in excess of the stress to which cervical vertebrae will be subject and greater also than clinical targets of 10,000 N. Devices so made do not fracture at failure but rather irreversibly compress.

Figure 7 illustrates this phenomenon. Failure at 13 kN is indicated by a slowly rising load at displacements greater than about 1.5mm. If the tested device had failed by fracture, a rapid drop in load would have resulted. The design of the IFD and the PLGA comonomer ratio (i.e., lactide:glycolide ratio) enable the device to function through the four stages of healing with progressive loss of mass and strength. In clinically stable situations, at the end of stage I, the device should retain 70-80% of its mechanical strength, and at the end of stage II, 50% of its strength should be retained. During stages III and IV, further slow degradation will occur with complete resorption by one year.

Prototype devices have been prepared for feasibility trials with goats as the animal model. A viable model for testing fusion materials in the cervical spine is the in vivo goat model. Unlike most quadrupeds, the goat holds its head erect, thus loading the cervical vertebrae in a manner similar to humans. Although there are geometric differences, the relative sizes of the disc and vertebral bodies are similar to those of the human. (Pintar et al., Spine 19:2524-2528, 1994; Zdeblick et al., Spine 17(105):5418-5426, 1992.) The goat is thus the animal model of choice for testing the spinal fusion device of the invention.

The experimental procedure followed in the in vivo goat model is as follows. Anesthetized animals undergo implantation via a surgery to the anterior cervical spine (Pintar et al., Spine 19:2524-2528, 1994). After exposing the lower 5 cervical segments, discectomy is performed at four levels. Two resorbable IFD's filled with cancellous

bone are placed in two of these spaces, the others receive a piece of tricortical iliac bone graft in place. The bone graft and cancellous bone are harvested from the goat iliac crest through a separate incision over the hip bone. Placement of the IFD or the graft in upper or lower sites is alternated for each animal with an intact disc space between implants. The operative sites are closed, and the animals allowed to recover.

At sacrifice, the spinal column of the goat is excised leaving the intact ligamentous column. The cervical and lumbar sites are separated and radiographed before mounting for biomechanical (as described above) or histological analyses for resorptive activity and new bone formation. The fusion rate and biomechanical stiffness are evaluated for spinal units harvested from the goats. Spinal units undergo radiographic imaging to assess fusion, biomechanical testing to assess strength, and histological analysis to assess tissue changes. The results are compared to conventional graft-based spacers and fusion devices.

PLGA implants can be effectively reinforced by the use of degradable scaffolds which are molecularly dispersed in the host PLGA polymer. For example, a solid solution containing PLGA, poly(propylene fumarate) (PPF), and vinyl pyrrolidinone (VP) as a crosslinking agent (or other vinyl monomer) may be heated with an initiator (such as benzoyl peroxide). The PPF chains are crosslinked by VP to form an interpenetrating network of crosslinked PPF and PLGA polymer chains. Following heating, further crosslinking is possible using  $\gamma$ -irradiation, e.g. 2.5 Mrad.

Several reinforcement techniques described in the literature include self-reinforcement using aligned PLGA fibers (Vainionpaa et al., Biomaterial 8:46-48, 1987; Pihlajamaki et al., J. Bone and Joint Surgery 74:13:853-857, 1992; Ashammakhi et al., J. Biomedical Materials

Research 29: 687-694, 1995) and reinforcement with calcium phosphate glass fibers (R.A. Casper et al., Polym. Mater. Sci. Eng. 53:497-501, 1985).

5 Reinforcement can also be achieved according to the invention by molding a rod of rectangular or other suitable cross-section that contains fibers under tension using the mold and ram assembly of the invention, as shown in Figs. 6A-6G. Referring to Fig. 6A, mold cavity 61 and ram 62 are rectangular in cross-section in the  
10 illustrated embodiment. The mold illustrated is constructed of five plates (front face plate 63, rear face plate 64, side plates 65 and bottom plate 66), suitably fastened or bonded together. The front and rear face plates 63, 64 are machined or otherwise formatted, as will  
15 be described below, with key holes 60 to receive holder assemblies for the reinforcing fibers, which comprise front and rear tension tubes, front and rear tension tube caps, serrated discs, and a front tension tube threaded nut.

20 Referring to Fig. 6B (an edge view of front face plate 63) and Fig. 6C (a plan view of front face plate 63), the inside face 67 of plate 63 contains a circular recess 68, with associated slots 69. Recess 68 adjoins a larger recess 70 that extends to the outside face 71 of  
25 front face plate 63. Recess 70 includes associated slots 72. The axis between slots 72 is perpendicular to the axis between slots 69. A smaller diameter recess stop 73 separates recess 68 from recess 70. Rear face plate 64 is similarly configured.

30 Referring now also to Figs. 6D-G, the mold is assembled for use as follows. A disc 75 (Fig. 6D) having serrated slots 76 is threaded with polymer fibers 88, which are distributed throughout the serrated slots. The distribution of the fibers is spatially maintained by the  
35 serrations. Referring also to Fig. 6G, discs 75 with fibers in place are mounted in recesses 68 in the front

and rear face plates 63, 64 of the assembled mold. Orientation of discs 75 is maintained by vanes 77 on the sides of the discs, which fit into slots 69.

Alternatively, discs 75 may be mounted first in face plates 63, 64 and threaded in place. The protruding fiber bundles are then threaded through front and rear tension tube assemblies 78, 79, which are positioned in recesses 70 in the front and rear face plates 63, 64, respectively.

Tension tube assemblies 78, 79 consist of tension tubes 80, each having vanes 82 which fit into slots 72 in the front and rear face plate recesses 70, respectively, thus maintaining the orientation of the tubes. The tension tubes are closed with caps 83 to complete assemblies 78, 79.

The fiber bundles are threaded additionally through holes 84 in the front and rear tension tube caps, as they exit the tension tubes. Holes 84 are off-center and below the axis of the tension tubes. This configuration holds the fibers against the serrations of the discs. Outside the caps, the fibers may be knotted to keep them from slipping back through the holes.

Other methods of anchoring the fibers may be used. For example, a bead of cement (such as epoxy or cyanoacrylate adhesives) may be built up on the outside of the caps to keep the fibers from slipping through. Also referring to Figs. 6E and 6F,

it can be seen that the tension tube 80 of front tension tube assembly 78 is exteriorly threaded 85 along its length and equipped with a nut 86 which, when tightened against the face plate, pulls the tension tube partially out of the face plate, thus putting the fibers under tension.

To prepare a reinforced resorbable spinal fusion device, mold cavity 61 of the assembled mold is then filled with the appropriate powdered formulation. The powdered formulation may be evenly distributed among the fibers by placing the mold on a vibrator. Ram 62 is put in place, in the opening of the mold, and pressure is



exerted. The mold may be heated externally with heating tapes, or it may be so machined as to have recesses for cartridge heaters. When the molding process is complete, the tension on the reinforcing fibers is released, and the  
5 completed device is removed from the mold.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223

While the present invention has been described in conjunction with a preferred embodiment, one of ordinary skill, after reading the foregoing specification, will be able to effect various changes, substitutions of  
5 equivalents, and other alterations to the compositions and methods set forth herein. It is therefore intended that the protection granted by Letters Patent hereon be limited only by the definitions contained in the appended claims and equivalents thereof.

THIS DOCUMENT CONTAINS NEITHER RECOMMENDATIONS NOR  
CONCLUSIONS OF THE NATIONAL BUREAU OF STANDARDS  
AND IS NOT INTENDED TO BE USED IN CONNECTION WITH  
THE NATIONAL BUREAU OF STANDARDS